

SISTEM DE SUPRAVEGHERE VIDEO PENTRU 32 CAMERE

I.D.: 50248859

Data publicarii 01.10.20 Coduri CPV 32323500-8

Pretul estimativ: 57.740,40 RON - 57.740,40 RON

Descriere: Sistem de supraveghere video compus din :Hard disk intern pentru echipamente de supraveghere Surveillance Series: 3.5"; SATA: 6Gb/s; 5400RPM; Buffer: 64MB; Capacitate: 4TB -2 BUC,Network Video Recorder 4K panou frontal cu touch; 32 Ch IP Video, 1 IN/1 OUT Ch Audio; lesiri Video: HDMI, VGA, MAIN; Rezolutie HDMI / VGA: 4K (3840 x 2160)/60Hz, 4K (3840 x 2160)/30Hz, Inregistrare/redare:8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF; Decodare:2-ch @ 4K/8-ch @ 1080p; Redare Sincrona: 16 Ch; 4 HDD Port SATA/6TB; 2 USB2.0; 1 USB3.0; 2 RJ45 10M/100M/1000M Ethernet; 1 RS-485; 1 RS-232; Alimentare:220VAC;Temperatura:-10°C~+55°C;Umiditate:10%~90%; Dimensiuni:445(W)x390(D)x70(H)mm;19-inch,rack-mounted,1,5U;Greutate:5Kg-1 BUC,Rack 19" , 540 * 450 mm, 6/9u , priza racabila , acesorii , repartitor-1 buc. Rack 19" , 540 * 450 mm, 19u , priza racabila , acesorii , repartitor-1 buc, Camera turbo HD LowLight, 2 Megapixel high-performance CMOS, LED Array EXIR 2.0, 40m, Bullet, ICR, 0.005 Lux/F2.0 AGC ON, Smart IR, 3D DNR, Meniu OSD(Coaxitron), 120dB WDR, IP67, Lentila2.8mm;DC12V/max. 5W-32 bucMonitor color , 21.5", LED-Backlit TFT LCD;HDMI, VGA; Rezolutie max.: 1920x1080; Timp raspuns: 5ms; Contrast: 1000:1; 250cd/m²; Unghi: H=170°, V=160°; OSD; HDMIx1; VGAx1;BNC: INx1, OUTx1; USBx1; Audio 1IN/1OUT; Difuzor:2x2W; Alimentare: AC 100~240V; Dimensiuni: 511mm*313mm*45mm; VESA 100mm x 100mm; Greutate: 3,2kg-1 buc,UPS 1500VA 900W afisaj LCD Input Voltage: 110/120 or 220/230/240VAC,Vo