

Comanda scrisa având ca obiect furnizarea a 2 seturi antene si receptor WAS/RLAN banda 5GHz.

I.D.: 9408593

Data publicarii	25.09.15	Coduri CPV	31711110-7
-----------------	----------	------------	------------

Termenul limita pentru depunere:	30.09.15	Pretul estimativ:	3.500,00 RON
----------------------------------	----------	-------------------	--------------

Descriere: Set antene si receptor WAS/RLAN compus din: a) Antena directiva cu reflector parabolic; Banda de frecventa- 5.1..5.8 GHz; câstig - 30dBi; polarizare - dual linear; VSWR - 1.4:1; Caracteristica de directivitate orizontala - 5 grade (3dB); Caracteristica de directivitate verticala - 5 grade (6dB); Raport fata/spate - -34dB; Izolare Cross-Pol - 35 dB min.; Impedanta - 50 ohmi; Diametru maxim - 650 mm; Greutate - 9,8 kg; Conectori - 2 x RP-SMA; Jumperi RF inclusi; Suport universal pentru stâlp inclus; Conform standard EN 302 326 DN2; b) Antena omnidirectionala; Banda de frecventa- 5.45..5.85 GHz; câstig - 10dBi; polarizare - dual linear; VSWR - 1.6:1; Caracteristica de directivitate verticala - 12 grade; Izolare Cross-Pol - 25 dB min.; Impedanta - 50 ohmi; Dimensiuni - 582x90x65 mm; Greutate - 0,68 kg; Conectori - 2 x RP-SMA; Jumperi RF inclusi; Suport universal pentru stâlp inclus; Conform standard EN 302 326 DN2; c) Receptor WAS/RLAN; Banda de lucru - 5GHz; Procesor - Atheros MIPS 74KC 400 MHz; Memorie - 128 MB SDRAM, 8MB Flash; Interfata de retea - 100Base-TX; Conectori - 2 x RP-SMA; Putere maxima - 27 dBm; Sensibilitate - -74 ... -96 dBm; Dimensiuni - 160x80x30 mm; Greutate maxima - 0.5 kg; Carcasa - plastic rezistent la ultraviolete; Sursa de alimentare - Passive POE, 24V, 1A; Temperatura de operare - -30 ... +75°C; Umiditate - 5 ... 95%; Moduri de lucru - Access Point, Station; Servicii disponibile - Web Server, SNMP, SSH Server, Telnet , Ping Watchdog, DHCP, NAT, Bridging, Routing; Utilitare - Antenna Alignment Tool, Discovery Utility, Site Survey, Ping, Traceroute, Speed Test; d) Cablu adaptor N mama - RP-SMA, cablu H155, lungime 1 metru - 2 buc.
