

amera supraveghere Speed Dome, 2 MP, IR 150 m, 4.8 - 135 mm

I.D.: 62914361

Data publicarii 10.11.21 Coduri CPV 42961100-1

Pretul estimativ: 3.025,22 RON - 3.025,22 RON

Descriere: Specificatii Camera Senzor: 1/2.8 inch Progressive Scan CMOS Rezolutie: 2 Megapixeli (Full HD - 1920 x 1080 pixeli) Viteza shutter electronic: PAL: 1/1 s - 1/10,000 s NTSC: 1/1 s to 1/10,000 s Sensibilitate: 0.005 Lux Distanta iluminator IR: 150 m Lentile Lentila varifocala: 4.8-153 mm Diafragma: F 1.2-F 4.4 Unghi de vizualizare: 55.6° - 2.04°; 32.4° - 1.14°; 63° - 2.34° (orizontala, verticala, diagonala) Distanta de focalizare: 100 - 1500 mm Viteza Pan: viteza Pan manuala: 0.1° - 120°/s viteza Pan presetata: 120°/s Miscare Tilt: -15° - 90° (auto flip) Viteza Tilt: viteza manuala Tilt: 0.1° - 80°/s Viteza presetata Tilt: 80°/s Numar presetari: 256 Tur: 10 (pana la 32 de presetari pe fiecare tur) Opreire memorie: Da Sarcini programate: Preset/Patrol/Pattern/Pan Scan/Tilt Scan/Panorama Scan/Day Mode/Night Mode/Zero Calibration/Patrol-d/None Video Cadre/secunda: 50 Hz: 25fps@(1920 x 1080) 60 Hz: 30fps@(1920 x 1080) Functii speciale: BLC, HLC, WDR (120 dB), 3D DNR, EIS, Zoom digital (16x) Intrare/iesire iesire Video: interschimbabil TVI/AHD/CVI/CVBS, (NTSC sau PAL composite, BNC) Alarma: 2 intrari alarma, 1 iesire alarma Interfata RS-485: Mod Half-Duplex Auto-adaptiv Hikvision, Pelco-P, Pelco-D protocol Functie UTC: protocol UTC General Grad de protectie: IP66, TVS 6000V Alimentare: DC 12V/3A; PoE+ Consum: 30 W (IR: 10 W) Temperatura de functionare: -30°C - +65°C Umiditate: ≤ 90 % Dimensiuni: ø 208 mm x 305 mm Greutate: 3.3 Kg Pachetul contine Camera supraveghere Speed Dome Hikvisi