

## Placa de baza Gigabyte Z590 AORUS ELITE AX, Socket 1200

I.D.: 62386808

Data publicarii 26.10.21 Coduri CPV 30237140-2 30230000-0

Pretul estimativ: 1.117,45 RON - 1.117,45 RON

Descriere: Placa de baza Gigabyte Z590 AORUS ELITE AX, Socket 1200 Specificatii PROCESOR CPU Socket 1200 Chipset Z590 Procesoare suportate Intel® Core™, Pentium® si Celeron®, generatiile 11 si 10 Socket-uri procesor 1 MEMORIE Tip memorie DDR4 Capacitate maxima memorie RAM (MB) 128 GB Frecventa memorie (MHz) 5400 (O.C)/ DDR4 5333(O.C.)/ DDR4 5133(O.C.)/DDR4 5000(O.C.)/4933(O.C.)/4800(O.C.)/ 4700(O.C.)/ 4600(O.C.)/ 4500(O.C.)/ 4400(O.C.)/ 4300(O.C.)/4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200 / 3000 / 2933 / 2800 / 2666 / 2400 / 2133 Suport Dualchannel Da Sloturi memorie 4 CONECTIVITATE Slot PCI PCI Express 4.0 x16 Audio integrat Realtek® ALC1220-VB LAN integrat Realtek® 2.5GbE LAN chip RAID integrat 0,1,5,10 Interfata Serial ATA 6 x SATA Rata de transfer SATA (MB/s) 6 Gb/s Conector sursa (pini) 1 x 24 pin ATX 1 x 8 pin ATX 1 x 4 pin 12V Conectivitate 5 x Audio Jacks 1 x SPDIF optical out 4 x USB 2.0 1 x DisplayPort 1 x RJ-45 2 x SMA Antena Connectors (2T2R) 3 x USB 3.2 Gen 1 port 1 x USB 3.2 Gen 2x2 2 x USB 3.2 Gen 2 Tip-A (rosu) SLOTURI Sloturi PCI-E x16 2 Sloturi PCI-E x1 1 Sloturi speciale 3 x M.2 ALTELE Tehnologii suportate Q-Flash Xpress Install APP Center Q-Flash Plus Wi-Fi 6 BIOS & memorie BIOS AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0 256Mb Flash ROM Format ATX Dimensiuni (L x W) (cm) 30.5 x 24.4