

Multimetru digital Rezistenta Izolatie Uni-T UT505 / Multimetru digital UNI-T UT70B

I.D.: 50183109

Data publicarii 28.09.20 Coduri CPV 38424000-3

Pretul estimativ: 1.234,00 RON - 1.234,00 RON

Descriere: Rezistenta de izolatie: Tensiune de testare: 50V / 100V / 250V / 500V / 1000V; 0% - 10% 50V: 0.01 MOhm ~ 50,0 MOhm; \pm (3% + 5) 100V: 0.01 MOhm ~ 100,0 MOhm; \pm (3% + 5) 250V: 0.01 MOhm ~ 200,0 MOhm; \pm (1,5% + 5) 500V: 0.01 MOhm ~ 500 MOhm; \pm (1,5% + 5) 1000V: 0,1 MOhm ~ 2000 MOhm; \pm (1,5% + 5) 2.0GOhm ~ 9.9GOhm; \pm (10% + 3) 10.0GOhm ~ 20Gohm; \pm (20% + 10) Curentul nominal: 50V (R = 50KOhm) 1mA 0% ~ 10% 100V (R = 100 KOhm) 1mA 0% ~ 10% 250V (R = 250 KOhm) 1mA 0% ~ 10% 500V (R = 500 KOhm) 1mA 0% ~ 10% 1000V (R = 1 MW) 1mA 0% ~ 10% Tensiune DC: 0.0V ~ 600.0V; \pm (2% + 3) Tensiune AC: 0.0V ~ 600.0V; \pm (2% + 3) Scalare automata RMS Masurare coeficient absorbtie: 60s /15s si 60s/ 30s Descarcare automata Opreire automata Continuitate Afisaj cu iluminare de fundal Indicator pentru baterie descarcata Alimentare: 6 x 1,5 V (LR6) Afisaj LCD: 62 x 53 mm, 3999 (3 $\frac{3}{4}$ diti) Tensiune DC: 400mV/4V/40V/400V/1000V, \pm (0.8%+1) Tensiune AC: 4V/40V/400V/750V, \pm (1.0%+5) Curent DC: 400 μ A/4mA/40mA/400mA/10A, \pm (1.0%+2) Curent AC: 400 μ A/4mA/40mA/400mA/10A, \pm (1.5%+5) Rezistenta: 400O/4kO/40kO/400kO/4MO/40MO, \pm (1.0%+2) Capacitate: 4nF/40nF/400nF/4 μ F/40 μ F/400 μ F/4mF/40mF \pm (4.0%+3) Temperatura: -40°C~1000°C \pm (1.0%+3), -40°F~1832°F \pm (1.0%+4) Frecventa: 4kHz/40kHz/400kHz/4MHz/40MHz/400MHz, \pm (0.1%+3) Viteza de rotatie (RPM): 40kRPM \pm (0.1%+3) Verificarea continuitatii cu buzzer Verificarea diodelor Registrare valori minime/maxime Masurare valori relative Memorarea datelor Scalare automata Interfata PC RS232 Afis