

AAA9E2AH42R/AAB Sistem de supraveghere video stradal cu 2 camere speed dome

I.D.: 49017172

Data publicarii	19.08.20	Coduri CPV	32235000-9
-----------------	----------	------------	------------

Pretul estimativ:	14.162,00 RON - 14.162,00 RON
-------------------	-------------------------------

Descriere: Sistem de supraveghere video stradal cu 2 camere speed dome (1 buc. Piata Smirodava, 1 buc. parcul bloc 30 Anton Pann). Camera IP PTZ 2 MP, zoom optic 20X, Senzor: 1/3", 2megapixel progressive scan CMOS, Rezolutie: 1080P@30fps (1920 x 1080), 720P;, Compresie: Ultra-H.265/H.265/H.264 /MJPEG, Iluminare minima: 0.03Lux (F1.5, AGC ON) ,0 Lux cu IR, Led IR: Smart IR 150M, IR-CUT; Lentila: 4.5-135mm, Zoom optic 30x (62.9° - 2.3°) PTZ: Pan Speed: 0.1°~300°/s, Tilt Speed: 0.1°~240°/s; Audio: IN/OUT; Alarma: 1IN/1OUT, LAN 10/100Mbps, Stocare: MicroSD max 128GB (neinclus); Functie ANR, Alimentare: 24 VAC, 24 VDC (inclus); Consum: max. 42W; Temp. operare: - 40 °C - 65 °C, IP66., Suport de perete inclus - 2 buc Fibra optica ADSS - A-DQ(ZN)2Y - AERIAN, unitube, gel filled, metalfree, longitudinal waterbloking, aramid yarns, invelis HDPE, protectie UV, distanta intre stalpi 30-60m (functie de diagrama conditii de instalare/conditii de mediu), 4 fibre - 100 m Cutie metalica 400x300x200 cm pentru echipamente - 2 buc Cutie suduri fibra optica de interior - 1 buc Patch cord fibra optica SM duplex SC-SC 3 metri - 2 buc Suduri fibra optica - 6 buc Media Converter 10/100Base-TX, 100Base-FX, sursa in comutatie cu o plaja larga de tensiuni de intrare (80-250V). 20km. 1550nmTX/1310nmRX. SM, conector SC, DIP Switch pentru configurarea diverselor stari de lucru - 2 buc Prelungitor 4 prize - 2 buc Intrerupator automat bipolar 10A - 2 buc Presetupe - 6 buc Patch cord FTP cat.5E ecranat 5 m - 2 buc.
