

## **Cerneală flexografică albă solvent HS3J-19888:SOLVASLEEVE EF WHITE MJ**

I.D.: 43236560

---

Data publicarii	20.06.19	Coduri CPV	22610000-9
-----------------	----------	------------	------------

---

Pretul estimativ: 4.020,00 RON - 4.020,00 RON

---

Descriere: HS3J-19888 Solvasleeve EF White 1. Description Solvent based ink for printing on films. White is suitable as well for outside/reverse printing on shrink substrates. Because of differences in the substrate, a test for mechanical resistances (adhesion, scratch, rub and wet rub) prior to printing is strongly recommended. 2. Product features\* • Excellent printability • Suitable for shrink and stretch process(flexible ink film) • NC compatible • Adjusted slip properties • Very good crinkle resistance • Very good scratch resistance • Very good rub resistance 3. Product Suitability\* 3.1 Applications HS3J-19888 is intended for use in the following areas: ■ Outside/reverse printing for shrink substrates ■ HS3J-19888 should not be used for other end uses without prior discussion with your local Sun Chemical representative and is not suitable for: ■ Direct food contact ■ Lamination \*Please refer to your local Sun Chemical representative for specific details. 3.2 Substrates HS3J-19888 is suitable for the following substrates: Primary Web Polyethylene, LDPE min. 38mN/m OPS Polyester (PET-G) Polypropylene PVC 4. Colour Range English Version 1 March 2016 Page 2/4 Technical Data Sheet 5. General Handling 5.1 Storage The inks are considered highly flammable. Suitable precautions should be observed to avoid ignition sources. Temperature of storage needs to be kept between 5°C and 35°C. Shelf life: 12 months under above conditions in tightly sealed containers. 5.2 Waste disposal Care should be

---