
ROTAVISC hi-vi II HELI Complete -Ref.60954 Cercetare Ctr.532PED/2020

I.D.: 56769308

Data publicarii	06.05.21	Coduri CPV	38432000-2 38425200-2
-----------------	----------	------------	-----------------------

Pretul estimativ: 17.673,25 RON - 17.673,25 RON

Descriere: Pachet vâscozimetru, include suport electric, palete Regardless of a simple or demanding viscosity measurement - IKA ROTAVISC hi-vi II HELI Complete determines the viscosity of extremely viscous liquids in all areas of application ranging from the laboratory to quality control. The scope of delivery includes a standard spindle set (SP 7-SP 12), a protective bracket, temperature sensor and HELISTAND stand incl. T-spindle set. Easy to operate The generous 4.3" TFT display allows for an intuitive menu guidance. A digital spirit level also supports the correct set-up of the start-up condition. The simple ramp function simplifies repetitive tasks. Highest measurement accuracy The level of measurement accuracy of the ROTAVISC rotational viscometer for both Newtonian and non-Newtonian fluids is +/- 1 % of the measuring range. The reproducibility is +/- 0.2 %. Stepless speed ROTAVISC is a viscometer, which offers stepless speed adjustment. Viscosity measurement in motion The motorized IKA HELISTAND moves the mounted viscometer and its rotating body slowly and uniformly up and down in the sample ROTAVISC hi-vi II HELI Complete Viscosity measuring range: 800 - 320.000.000 mPas Scope of delivery ROTAVISC hi-vi II HELI Complete SP set-2 PT 100.8 HELISTAND T-SP-SET
