

ECHIPAMENTE SUPRVEGHERE VIDEO

I.D.: 49141312

Data publicarii	26.08.20	Coduri CPV	32351000-8
-----------------	----------	------------	------------

Termenul limita pentru depunere:	28.08.20	Pretul estimativ:	9.500,00 RON - 9.500,00 RON
----------------------------------	----------	-------------------	-----------------------------

Descriere: SWICH UTP7524GE-MX 28 port SFP/ETH modular cu management =1buc,+modul SFP 8 port 155/1250Mbps=2buc+Rack 27U dulap metalic 600x600x1400 contine si unitventilație cu 2 ventilatoare=1buc+camera video NVR 32 canale HIKVISION DS-9632NI I8 H265 4K NetworkVideoRecorder 32 ch IP NetworkVideo Recorder pentru camere IP HIKVISION, 320Mbs incoming bandwidth + 256 Mbs out, inregistrare pana la 12MegaPixel/camera, maximum 32 camere IP, playback simultan maximum 16 canale, LIVE local display 32 camere 5MegaPixel pe 2 monitoare (16 fiecare) conectate la VGA 1 si VGA2, local playback sincron 1 camera 5Megapixel din 32 camere 5 MegaPixel inregistrate; la 24 camere 5MegaPixel inregistrate= 9 playback local display si LIVE display 2x 12 camere 5MegaPixel , 8 SATA interfaces HOT SWAP, RAID0, RAID1, RAID5, RAID10, maximum 10TB x 8=80TB, 1 eSATA interface, HDMI1: 4K (3840 x 2160)/60Hz, VGA1, HDMI2, VGA2 Full HD 1080p, 1920x1080pixeli, alarme In/Out 16/4, 1xUSB3.0, 2x USB2.0, 2x RJ-45 10/100/1000 Mbps=1 BUC,Camera supraveghere Hikvision IP bullet DS-2CD2T86G2-4I(2.8mm); 8MP; Acusens Pro Series; Human and vehicle classification alarm; Powered by Darkfighter; 1/2" Progressive Scan CMOS; rezolutie: 3840 x 2160 @ 20fps; iluminare: Color: 0.014 Lux @ (F1.6, AGC ON), 0 Lux with IR; compresie: H.265+, H.265, H.264+, H.264; lentila: 2.8mm, unghi vizualizare: horizontal FOV: 110.7°, vertical FOV: 59.1°, diagonal FOV: 131°, distanta IR: 80 metri; 120dB WDR/BLC/HLC/3D DNR/IR Cut Filter/ROI; Analiza imagine: depasire linie virtuala, detectie intrusi, detectie intrare-iesire perimetru, clasificare dupa oameni si masini; triple stream; slot micro SD/SDHC/SDXC slot, pana la 256 GB;=3 BUC
