

Microscop de fluorescenta pc EUROMEX - ref nr 3319 Chimie

I.D.: 71575485

22.07.22 Coduri CPV 38519610-5 38515200-0 Data

publicarii

Pretul 35.293,24 RON - 35.293,24 RON

estimativ:

Descriere: 1.1 Microscop de fluorescenta pc EUROMEX 22,905.02 12.18% 20,115.17 EWF 10x/22 mm eyepieces Trinocular version with Siedentopf 30° inclined tubes. Interpupillary distance 48-76 mm with diopter adjustment on left eyepiece Revolving quintuple reversed nosepiece on ball bearings Plan Fluarex PLFi 4x/0.10, 10x/0.25, S40x/0.65, S100x/1.25 oil immersion IOS objectives All optics are anti-fungus treated and anti-reflection coated for maximum light throughput 187/230 x 140 mm rackless stage equipped with integrated 79 x 52 mm mechanical stage Height adjustable Abbe N.A. 1.25 condenser with opening for optional sliders Coaxial coarse and fine adjustments with 200 graduations. Precision 1 μm, 0.2 mm per rotation. Total travel approximately 24 mm Rack-stop for protection of slides and objectives. Friction adjustment Diascopic intensity adjustable 3 W NeoLED™ Köhler illumination with Internal 100-240 V power supply (CE) 100W HBO mercury vapor fluorescence illumination attachment with 3-position. Supplied with fluorescence filters for Blue and Green excitation iCare Sensor: the illumination of the microscope automatically switches off when the microscopist steps away from his position, saving energy CSS - Cable Storage System. The Cable Storage System of the iScope allows the user to easily insert the power cable into the back of the instrument Paint with Antibacterial Protection Layer Supplied with power cord, 500 mA 250 V spare fuse, 5 ml immersion oil and dust cover in styrofoam