

Sistem TvCI

I.D.: 66581934

Data publicarii	21.02.22	Coduri CPV	35125300-2
-----------------	----------	------------	------------

Pretul estimativ: 8.615,60 RON - 8.615,60 RON

Descriere: - DVR Turbo HD with 8 channels, 2MP maximum recording resolution, 5MP for IP, Turbo HD/AHD/HDCVI/CVBS/IP compatibility, 1 x SATA, 4 TB/HDD, 2 x USB 2.0, 12 VDC power supply, plastic housing, dimensions 200 x 200 x 45 mm, weight 0.8 Kg - 1 buc - Camera bullet, Anhd de exterior , 2MP, IR 40m, fixed lens 2.8mm, DWDR, 2D DNR, BLC, HLC, 1 output hd analog - TVI/AHD/CVI/CVBS, IP67, 12VDC - 2 buc - Camera dome, de exterior, ANHD , 2MP, IR 25m, fixed lens 2.8mm, DWDR, 2D DNR, BLC, HLC, 1 output HD analog - TVI/AHD/CVI/CVBS, IP67, 12VDC- 5buc - Video transceiver AHD/TVI(TurboHD)/CVI/CVBS - 7 buc Distanta TVI - 100m (720p/1080p) Distanta AHD - 300m (720p/1080p) Distanta CVI - 400m (720p),250m (1080p) Distanta CVBS - 300m Banda frecventa 0~50MHz Cablu retea Cablu UTP 24-16 AWG (0.5-1.31mm) Tip cablu Cat5e/6 Protectie la supratensiuni Rejectie interferente Temperatura de operare 0 gr C ~ 55 gr C - Doza PVC IP 55 - 7 buc - HDD 2TB SATA, Seagate, seria Surveillance, special pentru DVR/NVR. Reducere de 10% in cazul in care se achizitioneaza impreuna cu un DVR/NVR/server! - 1 buc - Cutie metalica, vopsita electrostatic, dimensiune: 327x408x110 mm - 2 buc - Sursa in comutatie, iesire 12-14.5 VDC, curent maxim 10.5 A, protectie la suprasarcina / scurtcircuit, functie de incarcare acumulator, in carcasa metalica de protective - 1 buc - Cablu UTP CAT 5E, lungime 305m, diametru 0.82±0.04mm, continut cupru 99.95%, ISO/IEC11801, TIA-568-C.2 YD/T1019, material izolare HDPE, temperatura ambiental
