
ANALIZOR TOC/TN PROBE LICHIDE COMPATIBIL CU UNITATEA SSM-5000 SHIMADZU

I.D.: 102108879

Data publicarii	26.08.24	Coduri CPV	38434000-6
-----------------	----------	------------	------------

Pretul estimativ: 179.075,00 RON - 179.075,00 RON

Descriere: ANALIZOR TOC/TN PROBE LICHIDE COMPATIBIL CU UNITATEA SSM-5000 SHIMADZU Include: cod 638-91110-58 TOC-LCPN FA,E200 (ANALIZOR TOC) - 1 bucata Basic unit: - Measurement method: catalytic combustion at 680°C with NDIR-detection - Measurement range:,,TC:,,up to 30000 mg/L ,,TIC:,,up to 3000 mg/L - Detection limit:,,NPOC:,, 50 µg/L - Determination of the parameter TC, TIC, TOC ,(with difference method) and NPOC - Simple change of catalyst - Automatic injection with the well known syringe/slider technique (without septa) - ISP-module (integrated sample pre-treatment) for sample preparation: - Automatic dilution from factor 2 to 50 - Acidification and sparging for NPOC-method in the closed environment(free from environmental contamination) - TC-Multi-point calibration from one Stock solution - Automatic change of measurement parameter if the sample exceed the measurement range - Automatic calibration - EN 1484 conform Options: -,TNM-L, upgrade to measure Total Nitrogen (TNb) -,POC option, upgrade to addition method (TOC=NPOC+POC) -,SSM-5000A, upgrade to measure TOC in solids -,High Salt Kit to measure salted samples -,Small sample volume kit for small sample volumes -,Manual injection kit, Operation - PC-controlled TOC-Control L for TOC-L CPH to control the system completely via USB connection: User Friendly Interface -,Icons and functions are shown on large buttons -,Lists files being used by types, sorting by file name or creation date -,Samples can be inserted in the s
