

## Cutie conexiuni Ex e ATEX

I.D.: 45501990

---

Data publicarii	08.04.20	Coduri CPV	31224700-9
-----------------	----------	------------	------------

---

Pretul estimativ: 1.998,65 RON - 1.998,65 RON

---

Descriere: ATEX Junction Boxe - Type code: TB-P12/RO0184 Material: Glass fiber reinforced polyester (GRP) Dimensions (WxHxD): 400.0 x 250.0 x 120.0 mm Degree of protection: IP66 Certificates: ATEX, IECEX, GOST TC-RU, NEMA 4X Marking Terminal Boxes: II 2G Ex eb ia IIC/IIB/IIA T6/T5/T4 II 2D Ex tb IIIC T85°C/T100°C/T120°C Temperature class: T6 @ +50°C / T5 @ +55°C / T4 @ +60°C Assembled with: 30 pc. Terminal blocks - Screw type - UT 2.5 BL 2.5mmp Blue 30 pc. Terminal blocks - Screw type - UT 2.5 BL 2.5mmp Blue 4 pc. End bracket (screwless) - CLIPFIX 35-5 2 pc. End plate - D-UT 2,5/10 1 pc. Earth Continuity Plate 1 pc. Earth Stud M6 brass-bottom 2 pc. Rail: 1 Face Bottom: 3pc. KBAU3MBNC-WCLS M32x1.5 - 4 Function Orion Universal Ex-d IIC/Ex-e II / Ex-td Nickel Plated Brass Cable Gland Sealings Range: int.15-26&ext.20-33mm Complet Kit: Plastic Washer + Lock Nut Brass Face RIGHT: 16pc. EBU1MBNC-WCLS M20x1.5 - 1 Function Ex-d IIC/Ex-e II / Ex-td Nickel Plated Brass Cable Gland Non-Armored Sealings Range: 4,0-12,0mm Complet Kit: Shroud+Plastic Washer + Lock Nut Brass Face Left: 16pc. EBU1MBNC-WCLS M20x1.5 - 1 Function Ex-d IIC/Ex-e II / Ex-td Nickel Plated Brass Cable Gland Non-Armored Sealings Range: 4,0-12,0mm Complet Kit: Shroud+Plastic Washer + Lock Nut Brass

---