



UAP-AC-PRO/U6-PRO, WRL ACCESS POINT

I.D.: 88059547

Data publicarii	10.10.23	Coduri CPV	32421000-0
-----------------	----------	------------	------------

Pretul estimativ: 1.500,00 RON - 1.500,00 RON

Descriere: UAP-AC-PRO/U6-PRO, WRL ACCESS POINT Technical Specifications Mechanical Dimensions Ø196.7 x 35 mm (Ø7.7 x 1.4") Weight Without mount: 350 g (12.4 oz), With mount: 450 g (15.9 oz) Hardware Networking interface (2) GbE RJ45 ports Management interface Ethernet Bluetooth Power method PoE 48V Passive PoE Power supply UniFi PoE switch 48V, 0.5A PoE adapter (Included)* *5-packs do not come with PoE adapters. Supported voltage range 44—57V DC Max. power consumption 9W Max. TX power 2.4 GHz 5 GHz 22 dBm 22 dBm MIMO 2.4 GHz 5 GHz 3 x 3 3 x 3 Throughput rate 2.4 GHz 5 GHz 450 Mbps 1300 Mbps Antenna gain 2 GHz 5 GHz 3 dBi 3 dBi Button Factory reset Mounting Wall/ceiling (Included) Operating temperature -10 to 70° C (14 to 158° F) Operating humidity 5 to 95% noncondensing Certifications CE, FCC, IC Software WiFi standards 802.11 a/b/g/n/ac Wireless security WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES) BSSID 4 per radio VLAN 802.1Q Advanced QoS Per-user rate limiting Guest traffic isolation Supported Power save Supported WMM Voice, video, best effort, and background Concurrent clients 250+ Supported Data Rates (Mbps) 802.11a 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11b 1, 2, 5.5, 11 Mbps 802.11g 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n 6.5 Mbps to 450 Mbps (MCS0 - MCS23, HT 20/40) 802.11ac 6.5 Mbps to 1300 Mbps (MCS0 - MCS9 NSS1/2/3, VHT 20/40/80)
