

## Switch 8 porturi POE+

I.D.: 88023418

---

Data publicarii	09.10.23	Coduri CPV	32420000-3
-----------------	----------	------------	------------

---

Pretul estimativ: 550,00 RON - 550,00 RON

---

Descriere: Switch 8 porturi POE+ CARACTERISTICI HARDWARE Interfață • 8x 10/100/1000 Mbps RJ45 Ports • AUTO Negotiation • AUTO MDI/MDIX Rețea media • 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m) • 100BASE-TX: UTP category 5, 5e cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m) • 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m) Număr ventilatoare Fanless Physical Security Lock Yes Alimentare Externă External Power Adapter(Output: 53.5VDC / 1.31A) Packet Forwarding Rate 11.904 Mpps Porturi (RJ45) PoE • Standard: 802.3 af/at compliant • PoE Ports: Ports 1-4 • Power Supply: 64 W Tabelă de Adrese MAC 4K Jumbo Frame 16 KB Capacitate switching 16 Gbps Dimensiuni (L x l x H) 6.7x3.9x1.1 in (171x98x27 mm) Consum maxim • 5.39 W (220/50 Hz no PD connected) • 75 W (220/50 Hz with 64 W PD connected) Max Heat Dissipation • 18.38 BTU/h (no PD connected) • 225.75 BTU/h (with 64 W PD connected) CARACTERISTICI SOFTWARE Metodă de Transmisie Store-And-Forward Funcții Avansate • Compatible With IEEE 802.3af/at Compliant PDs • IGMP Snooping • Mac Address Auto-Learning And Auto-Aging • IEEE802.3x Flow Control • 802.1p/DSCP QoS ALTELE Certificări CE, FCC, RoHS Conținut Pachet • TL-SG1008P • Power Adapter • Installation Guide Mediu • Operating Temperature: 0-40 °C (32-104 °F); • Storage Temperature: -40-70 °C (-40-158 °F) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensin

---