

UPS AEG PROTECT D LCD 3000 VA

I.D.: 61537376

Data publicarii	01.10.21	Coduri CPV	31682530-4
-----------------	----------	------------	------------

Pretul estimativ: 5.975,00 RON - 5.975,00 RON

Descriere: UPS AEG PROTECT D LCD 3000 VA - Protejeaza servere, retele, aplicatii medicale, telecom, automatizari industriale, generale. Caracteristici: UPS Dubla Conversie 19" Rack Timp de transfer 0 ms Bypass static integrat Bypass Manual (6-10 kVA) integrat LCD configurabil Acumulatori Hot-Swappable Extindere autonomie Paralelizabil (6,10 kVA) Dimensiune (LaxlnxAd) [mm]: 482,6x88x608 mm Masa [kg]: 29.5 Tip: Online Dubla Conversie Nivel de zgomot @1m: <50 dB(A) Producator: AEG nr faze: 1/1 tehnologie: VFI Serie: PROTECT D Familia_de_proodus: PROTECT D LCD Varianta constructiva: Rack 19" Putere nominala [VA] : 3000 Putere nominala [W]: 2700 Factor de putere IESIRE (cosfi): 0.9 Functie convertizor 50/60 Hz sau 60/50 Hz: da Timp de incarcare acumulatori la 90% din capacitate: 3 ore Autonomie @ 50% sarcina: 14 minute Autonomie @ 100% sarcina: 6 minute Autonomie @50% sarcina cu + Battery Pack: 24 minute Autonomie @100% sarcina cu + Battery Pack: 51 minute Port comunicatie: USB si RS232 Software management: Compuwatch inclus SNMP: optional Intrare Tehnologie Redresor: IGBT Numar faze intrare: 1 Tensiune de intrare nominala Uin: 230 Vac Uin minim [Vac]: 120 Uin Toleranta - [%]: -50% Uin Maxim [Vac]: 276 Uin Toleranta + [%]: +20% Frecventa de intrare nominala: 50/60 Frecventa de intrare minima [Hz]: 47,5 Fin toleranta -: -5 Hz Frecventa de intrare maxima [Hz]: 63 Fin toleranta+: +5 Hz Curent de intrare maxim la sarcina nominala: 14 A Distorsiuni armonice curent redresor Thdi [%]: THDi <5% F
