

Camera de supraveghere IP exterior Dahua IPC-HFW1230S-0280B, 2 MP, IR 30 m, 2.8 mm

I.D.: 44958291

Data publicarii 16.12.19 Coduri CPV 35125300-2

Pretul estimativ: 5.850,90 RON - 5.850,90 RON

Descriere: Senzor: 1/2.7 inch, 2 Mp, progressive CMOS Rezolutie video: 2 Megapixeli (1920x1080 pixeli) Cadre pe secunda: 1-30 fps Lentila fixa: 2.8 mm Difragma: F2.0 Zoom digital: 16x Unghiul de vizualizare: 104° Viteza shutter electronic: Auto/Manual, 1/3~1/100000s Sensibilitate: 0.08Lux Distanta iluminator IR: 30m Numar LED-uri IR: 18 Bit rate: H.265: 12K ~ 6400Kbps/H.264: 32K ~ 10240Kbps Control bit rate: CBR/VBR Capacitate de stream: 2 stream-uri Functii speciale; Auto(ICR) / Color / B / W / BLC / HLC / DWDR, AWB (Auto/Manual), Gain control (Auto/Manual), 3D DNR, Smart IR Detectarea miscarii: Off / On, 4 zone Regiune de interes: Off / On, 4 zone (ROI) RAM/ROM: 256 MB /32 MB Ratie S/N: 50dB Control on/off IR: Auto/ Manual Declansare alarma: detectarea miscarii, manipularea video, schimbarea scenelor, deconectarea retelei, conflictul adreselor IP, accesul ilegal, anomalia de stocare IVS: tripwire, intruziune Compresie video: H.265/H.264H/MJPEG, H.265+/H.264+ Retea 1x: RJ-45 (10/100Base-T) Protocol: HTTP;HTTPS;TCP;ARP;RTSP;RTP;RTCP;UDP;SMTP;FTP;DHCP;DNS;DDNS;PPPoE;IPv4/v6;QoS;UPnP;NTP;Bonjour;IEEE 802.1x;Multicast;ICMP;IGMP;TLS Interoperabilitate: ONVIF Profile S&G, API Metoda de stream: Unicast / Multicast Numar utilizatori: 10 / 20 Software compatibil: Smart PSS, DSS, DMSS Telefoane compatibile: iOS, Android Alimentare: DC12V, PoE (802.3af)(Class 0) Consum: <5.5W Temperatura de functionare : -30° C ~ +60° C Grad de protectie: IP67 Carcasa: metal si plastic Dimensiuni: 70 mm x 164.7mm