

Profile LED moving head. Proiectoare Orientabile BUC 4

I.D.: 70787623

Data publicarii 04.07.22 Coduri CPV 31518600-6

Termenul limita pentru depunere: 07.07.22

Descriere: SPECIFICATIONS OPTICAL Light Source: 1 LEDs (CW) 500 W, (15.5 A), 6000 K, 30,000 hours life expectancyLight Source: 1 LED (RGB) 60 W, (3.2 A), 50,000 hours life expectancyColor Temperature (at full): 6000 KCRI: 95.6Beam Angle: 5° to 50°Field Angle: 6° to 54°Zoom Range: 5° to 58°Cutoff Angle: : 7° to 58°Lumens – Source: 20,672Lumens – Output: 10,549Illuminance (6.4°): 29,598 lux @ 5 mIlluminance (53.7°): 640 lux @ 5 mSelectable PWM: 20,000, 40,000 DYNAMIC EFFECTS Pan and Tilt: 540°/270°Pan and Tilt Ranges: 540°, 360°, 180° pan/270°, 180°, 90° tiltColors: 6 + white, split colors, continuous scroll at variable speedsColors: CMY flags, CTO flag, color correctionGobos (1): 7 + open (7 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speedsGobos (2): 8 + open (8 glass), continuous scroll at variable speedsGobo Size: Gobo Wheel 1 (rotating): 26.9 mm (outside), 22 mm (image)Gobo Size: Gobo Wheel 2: 26.9 mm (outside), 22 mm (image),Effect Wheel: 1 effectFraming Shutters: YesDimmer: ElectronicShutter/Strobe: ElectronicZoom: MotorizedFocus: MotorizedFrost: Variable Frost - MotorizedIris: Motorized – 15 LeafPrism: 5 Facets, round, motorized, rotatingStrobe Rate: 0 to 20 HzMove-in-Black: YesDim Curves: 4 CONSTRUCTION / PHYSICAL Dimensions: 17.0 x 10.8 x 31.1 in (433 x 276 x 792 mm)Weight: 75.5 lb (34.4 kg)Exterior Color: BlackHousing Material: High-impact flame-retardant Polymer CONNECTIONS Power Connection: Edison plug to Seetronic Powerkon IP65Power Input: Seetronic Powerkon IP65Data Connectors: 5-pin XLR, Amphenol XLR Net RJ45 connectors in/outCable Length (power): 5 ft (1.5 m) CONTROL Control Protocol: Art-Net, DMX, CRMX, RDM, sACNDMX Channels: 32 or 41Art-Net Channels: 32 or 41Modes/Personalities: 2 personalities (32, 41) ELECTRICAL Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)Power Linking: 2 units @ 100 V; 2 units @ 120 V; 4 units @ 208 V; 4 units @ 230 V; 4 units @ 240 VPower and Current: 650 W, 6.53 A @ 100 V, 60 HzPower and Current: 640 W, 5.45 A @ 120 V, 60 HzPower and Current: 639 W, 3.10 A @ 208 V, 60 HzPower and Current: 648 W, 2.82 A @ 230 V, 50 HzPower and Current: 654 W, 2.75 A @ 240 V, 50 Hz CERTIFICATIONS / QUALIFICATIONS CE, MET, FCCIP Rating: IP20, dry locationTemperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C) WHAT'S INCLUDED Maverick Silens 2 ProfileSeetronic Powerkon IP65 power cord2 Omega brackets with mounting hardwareGel Frame Holder and Gel Frame OPTIONAL ACCESSORIES Professional Clamps: CTC-50HC, CTC-50HCNSafety Cable: SC-07IP Rated Seetronic® Powerkon ExtensionsDMX cablesEthernet cables