
Camera supraveghere exterior IP Hikvision DS-2CD1053G0-I2C, 5 MP, IR 30 m, 2.8 mm, PoE

I.D.: 81169194

Data publicarii	20.04.23	Coduri CPV	32333200-8 32300000-6
-----------------	----------	------------	-----------------------

Pretul estimativ: 2.793,50 RON - 2.793,50 RON

Descriere: Specificatii Senzor: 1/2.7 inch CMOS Progressive Scan Rezolutie video: 5 MP (2560 x 1920 pixeli) Sensibilitate: color 0.01 lux @ (F2.0, AGC pornit), B/W 0 lux cu IR Viteza shutter electronic: 1/3 s - 1/100000 s Distanta iluminator IR: 30 m (EXIR 2.0) Lentila fixa: 2.8 mm Unghi de vizualizare: 98° orizontal, 71.7° vertical, 127° diagonala Ajustare unghi: Pan 0° - 360°, Tilt 0° - 180°, Rotation 0° - 360° Main stream: 50 Hz - 20 fps (2560 x 1920), 25 fps (2560 x 1440, 1920 x 1080, 1280 x 720); 60 Hz - 20 fps (2560 x 1920), 30 fps (2560 x 1440, 1920 x 1080, 1280 x 720) Sub-stream: 50 Hz - 25 fps (1280 x 720, 640 x 480, 640 x 360); 60 Hz - 30 fps (1280 x 720, 640 x 480, 640 x 360) Compresie video: Main stream - H.265+/H.265/H.264+/H.264; Sub-stream - H.265/H.264/MJPEG Video bit rate: 32 Kbps - 16 Mbps Tip H.264: Baseline Profile/Main Profile/High Profile Tip H.265: Main profile Setari imagine: saturatie, luminozitate, contrast, claritate, AGC, WB Functii generale: anti-flicker, heartbeat, mirror, protectie parola, privacy mask, watermark, filtru adresa IP Functii speciale: filtru IR cut, WDR (120 dB), BLC, 3D DNR, ROI (1 zona fixa pentru mainstream) Eveniment basic: detectia miscarii, manipulare video, exceptie Corelare: upload la FTP, notificare centru de supraveghere, exceptie Interfata Ethernet: 1x RJ45 10M/100M auto-adaptiv Protocol: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP™, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour, IPv4, UDP, SSL/TLS Live vie
