

Switch 24 porturi POE + 4 × Sloturi Gigabit SFP

I.D.: 87781891

Data publicarii	06.10.23	Coduri CPV	32420000-3
-----------------	----------	------------	------------

Pretul estimativ: 3.380,00 RON - 3.380,00 RON

Descriere: Switch 24 porturi POE + 4 × Sloturi Gigabit SFP CARACTERISTICI HARDWARE Standarde și Protocoale IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z, IEEE 802.3ad, IEEE 802.3x, IEEE 802.3az, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1p, IEEE 802.1x Interfață • 24 × 10/100/1000 Mbps Porturi RJ45 (Negociere automată / Auto MDI / MDIX) • 4 × Sloturi Gigabit SFP Rețea media • 10BASE-T: cablu UTP categoria 3, 4, 5 (maxim 100m) • 100BASE-TX / 1000Base-T: cablu UTP categoria 5, 5e sau mai mare (maxim 100m) • 1000BASE-X: MMF, SMF Număr ventilatoare 2 Alimentator 100-240V AC, 50/60Hz Porturi (RJ45) PoE+ • Standard: 802.3at/af compliant • Porturi PoE+: 24 • Power Supply: 250 W Porturi (RJ45) PoE • Standard: 802.3at/af compliant • PoE+ Ports: 24 Ports • PoE Power Budget: 250 W* Dimensiuni (L x l x H) 440 × 220 × 44 mm (17.3 × 8.7 × 1.73 inch) Montare Montare în Rack Consum maxim • 294.7 W (220 V/50 Hz) (cu 250 W PD conectat) Max Heat Dissipation • 1005.66 BTU/hr (220 V/50 Hz) (cu 250 W PD conectat) PERFORMANȚĂ Switching Capacity 56 Gbps Bandwidth/Backplane 56 Gbps Packet Forwarding Rate 41.7 Mpps Tabelă Adrese MAC 8K Packet Buffer Memory 4.1 Mbit Jumbo Frame 9 KB CARACTERISTICI SOFTWARE Calitatea Serviciului • 802.1p CoS/DSCP priority • 8 priority queues • Priority Schedule Mode - SP (Strict Priority) - WRR (Weighted Round Robin) • Queue Weight Config • Bandwidth Control - Port/Flow based Rating Limit • Smoother Performance • Storm Control - Multiple Control Modes(kbp
