
Incubator CO2, model CB170 standard - ven. ref. 1013306

I.D.: 44358850

Data publicarii	22.10.19	Coduri CPV	33152000-0
-----------------	----------	------------	------------

Pretul estimativ: 33.496,00 RON - 33.496,00 RON

Descriere: Temperature range: ambient temperature plus 4 °C to 60 °C Humidity range: 90 to 95% RH
CO₂ control range: 0 to 20 vol% CO₂ Tried-and-tested anti-contamination concept with 180 °C hot air sterilization Hot-air sterilizable CO₂ sensor with single-beam infrared technology
CO₂ gas-mixing jet with Venturi effect Intuitive touchscreen controller Internal data recording, can be read out in open format via USB interface Optimized double-pan humidification system with condensation protection 170 liters of extra space in the interior while maintaining the same footprint Stacking height of just 1.80 m for easy use of the top unit Fail-safe CO₂ automatic diagnosis system for protecting the pH of cell cultures DuoDoor™ system: Unit door and glass door can be opened with one handle Tightly sealed inner door made of tempered safety glass 3 perforated shelves, stainless steel Load per rack [kg] 10 Net weight of the unit (empty) [kg] 95 Permitted load [kg] 30 Internal dimensions Depth [mm] 505 Height [mm] 600 Width [mm] 560 Power frequency [Hz] 50/60 Rated Voltage [V] 200...240 CO₂ Incubator standard version (CO₂ control range: 0 to 20 vol% CO₂) Cod 9040-0131 Accesorii incluse: Gas cylinder connection set for CO₂, consisting of a gas tank pressure regulator with connection parts and 5-meter hose, cod 8012-0014
