

## Router Access Point AirEngine 5760-10

I.D.: 49726267

---

Data publicarii	15.09.20	Coduri CPV	32420000-3
-----------------	----------	------------	------------

---

Pretul estimativ: 66.906,00 RON - 66.906,00 RON

---

Descriere: AirEngine5760-10 mainframe (11ax, indoor, 2x2 dual bands, built-in smart antenna, GE, USB, BLE) Caracteristici principale: Dimensiuni (H x W x D): 47 mm x 200 mm x 200 mm Greutate: 1.05 kg Interfete: 1 x 10/100/1000M self-adaptive Ethernet interface (RJ45), 1 x USB Bluetooth: BLE5.0 Modul IoT extern: 1 x USB External IoT module (supporting ZigBee and RFID) Indicator LED: Power-on, startup, running, alarm, and fault states of the system. BLE: BLE5.0 Alimentare: DC: 12 V ± 10% , PoE power supply: In compliance with 802.3at. Consum maxim de putere: 15.8 W Temperatura de operare: -10°C to +50°C Temperatura de stocare: -40°C to +70°C Umiditate in operare: 5% to 95% (non-condensing) Rezistenta la praf: IP41 Altitudine: -60 m to +5000 m Presiune atmosferica: 53 kPa to 106 kPa Tipul antenei: Built-in smart antennas Castigul antenei: 2.4G: 3.5 dBi, 5G: 5 dBi Numar maxim SSIDs: ≤ 16 Numar maxim de utilizatori: ≤ 512 Putere maxima transmisa 2.4G: 25 dBm (combined power), 5G: 25 dBm (combined power) Crestere in putere: 1 dBm Numar maxim de canale fara overlapping 2.4 GHz (2.412 GHz to 2.472 GHz) 802.11b/g – 20 MHz: 3 802.11n – 20 MHz: 3 – 40 MHz: 1 802.11ax – 20 MHz: 3 – 40 MHz: 1 5 GHz (5.18 GHz to 5.825 GHz) 802.11a – 20 MHz: 13 802.11n – 20 MHz: 13 – 40 MHz: 6 802.11ac – 20 MHz: 13 – 40 MHz: 6 – 80 MHz: 3 – 160 MHz: 1 802.11ax – 20 MHz: 13 – 40 MHz: 6 – 80 MHz: 3 – 160 MHz: 1

---