

## Camera supraveghere IP Dome Hikvision AcuSense DarkFighter DS-2CD2186G2-ISU, 8 MP, IR 30 m, 2.8 mm,

I.D.: 62413686

Data publicarii 27.10.21 Coduri CPV 35125300-2

Pretul estimativ: 2.521,05 RON - 2.521,05 RON

Descriere: Specificatii DS-2CD2186G2-ISU: Senzor: 1/1.8 inch Progressive Scan CMOS Rezolutie: 8 Megapixeli (4K - 3840 x 2160 pixeli) Sensibilitate: 0.003 LUX (0 LUX cu iluminator IR) Viteza shutter electronic: 1/3 s - 1/100.000 s Lentila fixa: 2.8 mm Diafragma: F1.6 Unghi de vizualizare: 111°, 59°, 131° (orizontala, verticala, diagonala) Distanta iluminator IR: 30 m Lungime de unda: 850 nm Main Stream: 50 Hz: 25 fps (3840 x 2160, 3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720) 60 Hz: 24 fps (3840 x 2160)/30 fps (3200 x 1800, 2688 x 1520, 1920 x 1080, 1280 x 720) Sub Stream: 50 Hz: 25 fps (640 x 480, 640 x 360) 60 Hz: 30 fps (640 x 480, 640 x 360) Third Stream: 50 Hz: 10 fps (1920 x 1080, 1280 x 720, 640 x 480, 640 x 360) 60 Hz: 10 fps (1920 x 1080, 1280 x 720, 640 x 480, 640 x 360) Compresie video: Main stream: H.265/H.264/H.265+/H.264+ Sub-stream: H.265/H.264/MJPEG Third stream: H.265/H.264 Rata de biti video: 32 Kbps - 16 Mbps Control Bit Rate: CBR/VBR Audio: Tip audio: mono sound Filtrare zgomot: Da Rata de esantionare audio: 8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz Compresie audio: G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC Rata de biti audio: 64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 - 192 Kbps (MP2L2)/8 - 320 Kbps (MP3)/16 to 64 Kbps (AAC) Interschimbare zi/noapte: zi/noapte/auto/programabil Ajustare imagine: Modul de rotatie, saturatie, luminozitate, contrast, claritate, AGC si balans de alb reglabil din software-ul clientului sau de b