

SIRIUSi-6xACC2xACC+

I.D.: 60956959

Data
publicarii 13.09.21

Coduri CPV 38434400-0

Pretul
estimativ: 65.340,00 RON - 65.340,00 RON

Descriere: 8 channel isolated SIRIUS slice, Input modes: Voltage, IEPE, Voltage ranges (DualCore): $\pm 10(0.5)$ V, IEPE Excitation: 2, 4, 8, 12, 16 or 20 mA, Input coupling: DC or AC (0.1 Hz or 1Hz), A/D converter: DUAL CORE (2 x 24 Bit sigma delta), 204.8 kS/s, with AAF, TEDS, Input connector: BNC, 2 Advanced counter for Event-, Timing- and Sensor mode on Lemo L1B7f, 1x CAN 2.0b BUS isolated on DSUB9m, 2x SYNC, USB2 interface, 9-36VDC supply, Dewesoft-X included DEWESOFT-X-PROF: The Professional license gives you access to the core functionality of the Dewesoft X software. Even though this is a base version, it is equipped with a wide range of features ranging from standard mathematical analysis, visualization, sequencing and exporting data to a multitude of formats. DEWESOFT-X-DSA: The DSA license is the perfect software solution for any and all digital signal processing. It covers a wide range of Noise & Vibration applications and offers options such as the FFT analyzer with extended cursor functionalities, order tracking, torsional vibration, rotor balancing, human body vibration, modal analysis, shock response spectrum as well as the sound level meter.