

sistem monitorizare video

I.D.: 44926349

| | | | |
|-----------------|----------|------------|------------|
| Data publicarii | 13.12.19 | Coduri CPV | 32323500-8 |
|-----------------|----------|------------|------------|

Pretul estimativ: 41.176,47 RON - 41.176,47 RON

Descriere: Sistem monitorizare video NVR Hikvision 64 canale ; 12MP; H.265/H.264/MPEG4 videoformats; Recording at up to 12 MP resolution; HDMI1 Video output at upto 4K (3840 x 2160) resolution; Up to 16 SATA interfaces and 1 eSATAinterface; 2 self-adaptive 10M/100M/1000M network interfaces; VCA detection alarm is supported 1 buc Camera de supraveghere Hikvision IP Cube ; 5MP; 1/2.5 Progressive Scan CMOS; H Color: 0.01lux@(F1.2, AGC ON), 0 lux with IR; 20fps(2560x1920), 25fps/30fps (2560x1440, 2048x1536, 1920x1080); 2.8mm lens; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 10m; DC12V and PoE; Built-in mic and speaker; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service*-W model: built-in WIFI. 27 buc Camera de supraveghere IP Dome ; 1/2.5 Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@ (F1.2, AGC ON), 0 lux with IR; 20fps(2560x1920), 25fps/30fps(2560x1440, 2048x1536, 1920x1080); 2.8-12mm motorized VF lens; 120dBWDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67, IK10; DC12V and PoE; Built-in microSD/SDHC/SDXC slot; HIK-Connect cloud service. 2.00 UPS nJoy Balder 1500, 1500VA/ 1500W, On-line, LCD Display, Montare Rack/Tower, 8 Prize IEC 13, Dubla conversie, Plaja larga de tensiuni acceptate, Eficienta impresionanta de pana la 96%, Frecventa: 40Hz ~ 70 Hz, Dimensiuni: 410 x 438 x 88 mm, Greutate: 15.5 kg 1 buc Switch POE cu web management, ; L2, Web managed, 16* 100M PoE port, 2*
