

## Sistem bariera-R391

I.D.: 100355229

---

Data publicarii	22.07.24	Coduri CPV	34926000-4
-----------------	----------	------------	------------

---

Pretul estimativ:	21.505,00 RON - 21.505,00 RON
-------------------	-------------------------------

---

Descriere: Oferta refuzata: 1.NVR 4K, 8 canale 12MP + 8 porturi PoE - HIKVISION - DS-7608NI-I2-8P Inregistrare:12MP/8MP/5MP/3MP/1080P/720P @25fps/ch Compresie: H.265+/H.265/H.264; Latime banda: intrare 80Mbps / iesire 256Mbps Analiza video: Search content, ANPR/LPR, VCA detection, temperatura, etc; Iesiri video: HDMI 4K (3840 x 2160), VGA 1080P Interfete externe: 2xUSB, LAN 10/100/1000Mb, 1 audio; Porturi PoE: 8 porturi RJ45 10/100 Mb (max. 120W) Capacitate HDD: 2xHDD max 8TB Tensiune alimentare: 220VAC, Consum: <15W (fara HDD) Dimensiuni: 385 x 315 x 52 mm. 1.415,00 lei 1 1.415,00 lei 2. ANPP - Camera LPR 4.0MP cu AI, DarkFighter, lentila 2.8-12 mm, IR 50m, Audio, Alarma -HIKVISION - iDS-2CD7A46G0-P-IZHSY(2.8 12mm) Senzor: 1/1.8" Progressive Scan CMOS, DarkFighter low-light performance; Rezolutie: 4MP (2688x1520)/ 1080P / 720P@30fps; Compresie: H.265+/H.265/H.264+/H.264/MJPEG; Iluminare minima: 0.0005 Lux @ (F1.2, AGC ON), B/W: 0.0001 Lux, 0 lux cu IR; Led IR: distanta IR 100M, IR-CUT, WDR: 140dB; Lentila: 2.8-12 mm - AUTOFOCUS (42.5° - 15.1°); Inregistrare: Micro SD pana la 256 GB; Interfata comunicare: 1 x RJ45 10/100/100M, 1 x RS485; Wiegand; Alarma: 2 IN/2 OUT; Audio: 1IN / 1 OUT; Iesire alimentare: 12 VDC, max. 100 mA; Alimentare: 12 V DC ± 20% , PoE(802.3at); Consum: max. 16.8W; Protectie antivandal: IK10; Temp. operare: -40 °C +60 °C , IP67; Dimensiuni: Ø 140 x 351 mm; Greutate: 1950g. 2.520,00 lei 2 5.040,00 lei 3. KIT complet bariera acces AUTO / 6 m, montaj universal ST/DR - MOTORLINE pentru tra

---