
Sursă de alimentare electrică continuă - UPS (server-PC)

I.D.: 63417797

Data publicarii	24.11.21	Coduri CPV	31154000-0
-----------------	----------	------------	------------

Pretul estimativ: 28.211,00 RON - 28.211,00 RON

Descriere: UPS SERVER RETEA: UPS APC Smart-UPS SRT 10000VA RM 230V srt10krmxli Putere (VA):10000; Montabile in rack; Intrari: Hard Wire 5-wire (3PH + N + G);Input Connections: Hard Wire 3 wire (1PH+N+G); Input Frequency : 45 - 65 Hz (auto sensing) Nominal Input Voltage: 230V, 400V 3PH; Other Input Voltages: 220, 240, 380, 415 V; Iesiri: Nominal Output Voltage: 230V; Other Output Voltages 220, 240 V; Output Connections: 1 x Hard Wire 3-wire (H N + G); 6 x IEC 320 C13; 4 x IEC 320 C19; 3 x IEC Jumpers; Output Frequency (sync to mains) 50/60Hz +/- 3 Hz Output Voltage Distortion Less than: 3% Interfata: Contact Closure, RJ-45 10/100 Base-T, RJ-45 Serial, Smart-Slot, USB; Baterie:Replacement Battery APCRBC140;Expected Battery Life 3 - 5ani Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof; Alarma:Audible and visible alarms prioritized by severity; Emergency Power Off (EPO) ; T. reincarc:1.50 h Altele:Battery Directive: Compliant; Battery Notes: Contains Lithium Coin Cell Bypass: Internal Bypass (Autom.+ Man.) Control panel: Multi-function LCD status and control console Crest Factor: 3 : 1 Max Configurable Power : 10 kW / 10 kVA Online Thermal Dissipation: 2002.00 BTU/hr Protection Class: IP 20 RBC Quantity: 2 REACH REACH: Contains No SVHCs Rack Height: 6U RoHS: Compliant Surge energy rating: 480 Joules Topology: Double Conversion Online Waveform : Type Sine wave Dimensiuni : 263 x 432 x 715 mm Greutate (Kg):111.82 KG Tens 220,240,380, 415V R nec 5790/1.10.2021
