

Statie grafica Fujitsu CELSIUS R970B

I.D.: 48859956

Data publicarii	11.08.20	Coduri CPV	30213300-8 30213000-5
-----------------	----------	------------	-----------------------

Pretul estimativ: 14.501,00 RON - 14.501,00 RON

Descriere: Statie grafica Fujitsu CELSIUS R970B Base unit: System board D3488, Chipset: Intel C624; Fujitsu Teutates system management controller, 1000 W wide range power supply; prepared for rack mounting (rack mount kit optionally available), EraseDisk and DeskView license included. Slots: 16 DIMM-slots (8 Slots per CPU), 7 expansion slots: 4x PCIe Gen3 x16, 2x PCIe x4 Gen2, 1x PCI32 1 internal expansion slot: PCIe x8 Gen3 2nd CPU (CPU1) is needed for the usage of three or four PCIe x16 add on cards and internal expansion slot. Onboard I/O devices: 2x 1Gbit network controller, SATA controller (10x SATAIII 6Gbit/s), HD-Audio Codec, Bays: 1x 5,25" und 2x 3,5" FlexiBays externally accessible, 4x 3,5" internal HDD bays or [2x 3,5" internal HDD bays and 2x 2,5" internal HDD/SSD bays] or [8x 2,5" internal HDD/SSD bays] - all internal HDD bays accessible from the front. Interfaces: Front interfaces: 2x USB 2.0, 2x USB 3.1 Gen1, 1x audio out, 1x audio in, Rear interfaces: 2x LAN RJ45, 2x USB 3.1 Gen1, 4x USB 2.0, 1x audio in, 2x audio out, Security: Embedded security (TPM 2.0) - Infineon Disable/Hide TPM option EraseDiskin, in urmatoarea configuratie: S26361-F5013-E208, Intel Xeon Silver 4208 8C 2.10GHz - 1 buc S26361-F5014-E208, 2nd Xeon Silver 4208 8C 2.10GHz - 1 buc S26361-F4104-E426, 8GB DDR4-2933 rg ECC - 2 buc S26361-F3300-E211, AMD Radeon Pro WX 2100 2GB - 1 buc S26361-F2391-E11, MiniDP / DP adapter cable - 2 buc S26361-F3420-E550 - DVD SuperMulti SATA - 1 buc S26361-F3924-E100, HDD SA
