

Camera supraveghere exterior IP Dahua IPC-HFW5541T-ASE-0280B, 5 MP, IR 80 m, 2.8 mm, PoE

I.D.: 84156075

Data publicarii	29.06.23	Coduri CPV	35125000-6
-----------------	----------	------------	------------

Pretul estimativ: 7.728,00 RON - 7.728,00 RON

Descriere: Specificatii Senzor: 1/2.7 inch, CMOS Progresiv Rezolutie video: 5 Megapixeli (2592x1944 pixeli) ROM/RAM: 128 MB / 512 MB Viteza shutter electronic: 1/3 s-1/100000 s Sensibilitate: 0.005 LUX Distanta iluminator IR: 80 m Numar LED-uri: 4 Lentila fixa: 2.8 mm Diafragma: F1.6 Unghiul de vizualizare: H:102°, V:71° Pan/Tilt: 0-360°/0-90°, rotatie 0-360° Distanta minima de focalizare: 0.9 m Detectie faciala Protectie perimetrala: Tripwire (linie virtuala), intruziune, miscare rapida (recunoastere vehicul si persoana), filtru vagabondaj, detectie parcare si adunare de persoane, contor trafic persoane Declansare alarma: detectarea miscarii, manipularea video, schimbarea scenelor, deconectarea retelei, conflictul adreselor IP, accesul ilegal, anomalii de stocare Compresie video: H.265,H.264,H.264B,H.264H, MJPEG Smart codec: da Main stream: 2592 × 1944 (1 fps-20 fps), 2560 × 1440 (1 fps-25/30 fps), 1920 × 1080 (1 fps-50/60 fps) Sub stream 1: D1 (1 fps-20/30 fps), D1 (1 fps-50 fps) Sub stream 2: 1080P (1 fps-17 fps) Rata de biti: H.264: 32 Kbps-8192 Kbps, H.265: 19 Kbps-8192 Kbps Functii speciale: Auto(ICR), BLC, HLC, WDR 120dB, Gain Control, 3D DNR, detectie miscare (4 zone), RoI (4 zone), Privacy Masking (4 zone), Mirror, Defog, Smart IR Compresie audio: G.711a, G.711Mu, G.726, AAC, G.723 Retea: RJ-45 (10/100 Base-T) Protocol: IPv4;IPv6;HTTP;HTTPS;TCP;UDP;ARP;RTP;RTSP;RTCP;RTMP;SMTP;FTP;SFTP;DHCP;DNS;DDNS;QoS;UPnP;NTP;Multicast;ICMP;IGMP;NFS;PPPoE;802.1x;SNMP Interoperabilitate: ONVIF
