



## Cititor de coduri de bare DS2208-SR BLACK USB KIT

I.D.: 41883917

Data publicarii 01.02.19 Coduri CPV 30216130-6

Pretul estimativ: 652,00 RON - 652,00 RON

Descriere: Cititor de coduri de bare DS2208-SR BLACK USB KIT: DS2208-SR00007ZZWW SCANNER, CBA-U21-S07ZBR SHIELDED USB CABLE Scanning Scanner type 1D/2D Sensor type LED Linear (1D) barcodes supported Codabar,Code 11,Code 128,Code 39,Code 93,EAN-13,GS1 DataBar Expanded,Interleaved 2 of 5,MSI,U.P.C. 2D (matrix & stacked) barcodes supported Aztec Code,Composite Codes,Data Matrix,Han Xin,MaxiCode,Micro QR Code,PDF417,TLC-39 Optical sensor resolution (W x H) 640 x 480 pixels Working distance 36.8 cm Wavelength 645 nm Motion tolerance (cm/s) 13 Tilt reading angle -65 - 65° Pitch reading angle -65 - 65° Yaw reading angle -65 - 65° Ports & interfaces Connectivity technology Wired Interface USB + RS-232 + RS-485 + Keyboard Wedge Wireless range 10 m Bluetooth version 4.0 BLE Design Product colour Black Type Handheld bar code reader International Protection (IP) code IP42 LED indicators RoHS compliance Certification EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/CSA-C22.2 No. 60950-1-07 IEC 62471 EN 55022 (Class B); EN 55032 (Class B) EN 55024 EN 61000-3-2 EN 61000-3-3 47 CFR Part 15, Subpart B, Class B ICES-003 Issue 6, Class B Power Power source type DC Battery technology Lithium-Ion (Li-Ion) Battery capacity 2400 mAh Battery life 100 h AC adapter output voltage 5 V Power consumption 250 mA Operational conditions Operating temperature (T-T) 0 - 50 °C Storage temperature (T-T) -40 - 70 °C Operating relative humidity (H-H) 5 - 95% Weight & dimensions