

Achiziție DVR Hikvision

I.D.: 71602774

Data publicarii	22.07.22	Coduri CPV	32331500-7
-----------------	----------	------------	------------

Pretul estimativ: 142,85 RON - 142,85 RON

Descriere: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 Rezolutie codificare: Cand 1080p Lite nu este activat: 720p/WD1/4CIF/VGA/CIF Cand 1080p Lite este activat: 1080p lite/HD 720p lite/WD1/4CIF/VGA/CIF Cadre/secunda: Main Stream: Cand modul 1080p Lite este activat: 1080p lite/HD 720p lite/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) Cand modul 1080p Lite nu este activat: Pentru stream de 720p: 720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) Pentru stream SD: WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) Sub Stream: CIF/QVGA/QCIF@25fps (P)/30fps (N) Bit Rate: 32Kbps la 4 Mbps Compresie audio: G.711u Video si audio Intrare video IP: 1 canal Pana la rezolutie 1080p Suporta camere IP H.265+/H.265/H.264+/H.264 Intrare video analogica: 4 canale Interfata BNC (1.0 Vp-p, 75 Ω), sustine conexiuni coaxitron Camere suportate: AHD - 1080p25, 1080p30, 720p25, 720p30 HDCVI - 1080p25, 1080p30, 720p25, 720p30 CVBS Iesire video: VGA/HDMI - 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz Intrare/iesire audio: 1 canal (RCA) / 4 canale (prin cablu coaxial) Comunicare bidirectionala: Refolosire primul canal audio Retea Interfata: 1x Port RJ-45 (10/100M) Protocol retea: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS Utilizatori simultani: 32 Stocare HDD: 1x port SATA, pana la 4TB Interfete auxiliare USB: 2x porturi USB 2.0 Caracteristici generale Temperatura de functionare: de la -10 pana la +55 grade Celsius Alimentare: 12 VDC, 1.5 A Consum: ≤ 16W
