

## ANALIZOR TOC/TN PROBE LICHIDE COMPATIBIL CU UNITATEA SSM-5000 SHIMADZU

I.D.: 101931271

Data 26.08.24 publicarii Coduri CPV

38434000-6

Pretul	178.000,00 RON - 178.000,00 RON
estimativ:	

Descriere: Oferta refuzata: ANALIZOR TOC/TN PROBE LICHIDE COMPATIBIL CU UNITATEA SSM-5000 SHIMADZU Include: 10 638-91110-58 TOC-LCPN FA,E200 (ANALIZOR TOC) - 1 bucata Basic unit: - Measurement method: catalytic combustion at 680°C with NDIR-detection -Measurement range:,,TC:,,up to 30000 mg/L ,,,,,,,,IC:,,up to 3000 mg/L - Detection limit:,,,, 50  $\mu$ g/L - Determination of the parameter TC, TIC, TOC ,,(with difference method) and NPOC -Simple change of catalyst - Automatic injection with the well known syringe/slider technique (without septa) - ISP-module (integrated sample pre-treatment) for sample preparation: -Automatic dilution from factor 2 to 50 - Acidification and sparging for NPOC-method in the closed environment(free from environmental contamination) - TC-Multi-point calibration from one Stock solution - Automatic change of measurement parameter if the sample exceed the measurement range - Automatic calibration - EN 1484 conform Options: -,,TNM-L, upgrade to measure Total Nitrogen (TNb) -,,POC option, upgrade to addition method (TOC=NPOC+POC) -,,SSM-5000A, upgrade to measure TOC in solids -,,High Salt Kit to measure salted samples -,,Small sample volume kit for small sample volumes -,,Manual injection kit, Operation - PCcontrolled TOC-Control L for TOC-L CPH to control the system completely via USB connection: User Friendly Interface -,, Icons and functions are shown on large buttons -,, Lists files being used by types, sorting by file name or creation date -,,Samples can be inserted in the sa